



WA90

Wylde Audio Phase

Celebrate the 20th anniversary of the explosive collaboration between Dunlop and Zakk Wylde with the MXR[®] Wylde Audio Phase. This pedal adds dimension and dynamics to Zakk's legendarily blazing solos and razor sharp leads—all with the twist of a single Rate knob.

External Controls



- 1 FOOTSWITCH toggles effect on/bypass (red LED indicates on)
- 2 SPEED knob controls overall effect rate

Basic Operation

Power

The MXR® Wylde Audio Phase is powered by a single 9-volt battery (remove bottom plate to install), a 9-volt AC adapter such as the Dunlop ECB003, or an MXR® Brick™ Series power supply.

Directions

- 1.** Run a cable from your guitar to the WA90's INPUT jack and run another cable from the WA90's OUTPUT jack to your amplifier.
- 2.** Start with the SPEED control at 12 o'clock. Turn the effect on by depressing the footswitch.
- 3.** Rotate the SPEED knob clockwise for a faster phase effect or counterclockwise for a slower phase effect.

Specifications

Input Impedance	1 MΩ
Output Impedance	10 kΩ
Noise Floor*	< - 96 dBV
Bypass	Hardwire
Current Draw	5 mA
Voltage Requirements	9 volts DC

*Tone controls center, all others max CW, A-weighted